

Squash Court Paint SQ1

● Technical Specification

DESCRIPTION

A superior quality solvent borne coating based on the best quality pigments and alkyd resins.

USES

Specially formulated to be used in the painting of walled areas around squash courts and other leisure pursuit areas.

CHARACTERISTICS

Squash Court Paint has excellent opacity.

The paint provides excellent adhesion over most surfaces.

When the surface is fully cured it may be washed repeatedly.

Squash Court Paint is non-toxic and is manufactured with minimum quantities of non-aggressive solvents.

PERFORMANCE

Squash Court Paint is quick drying. Shows outstanding durability.

FINISH

Smooth, matt finish.

COLOUR

White, Pale Blue, Pale Green.

ENVIRONMENTAL CONSIDERATIONS

Contains no added lead.

PACKAGING

5 Litres.

● Technical Specification

COMPOSITION

Alkyd resin with special pigments and additives.

PROPERTIES

VOC content: 416g/l

Cat. I: 600g/l (2007)/500g/l (2010)

● Surface Preparation

All surfaces must be properly prepared to ensure that they are dry, clean and free from rubber, oil and grease.

Glossy surfaces should be well abraded to improve adhesion. Remove all loose and flaking materials and prime where necessary with the appropriate primer or thinned Squash Court Paint.

● Application

METHOD

Brush, roller, conventional or airless spray.

Apply two coats of Glixtone Squash Court Paint.

COVERAGE

10-12 m² per litre.

DRYING TIME

Under normal atmospheric conditions.

Touch dry: 2-3 hours

Re-coatable: 5-6 hours

THINNING

Thin 10% with white spirit if required.

● Health & Safety Notes

Warning: This product is FLAMMABLE.

Flash Point: 41°C

Ensure good ventilation during application and drying.

Avoid contact with eyes and skin.

In case of contact with eyes:

Rinse immediately with plenty of water and seek medical advice.

In case of contact with skin:

Wash immediately with plenty of soapy water or a proprietary skin cleanser.

DO NOT USE SOLVENT, THINNERS OR WHITE SPIRIT.

Exclude sources of ignition during application and drying.

No smoking.

When spraying:

- Do not breathe spray

- Wear suitable respiratory protective equipment.

- Keep out of reach of children.

STORAGE

Store in secure, dry conditions. Containers should be kept closed during storage. Do not store near oxidising agents. Avoid spillage and contamination. Do not empty into drains and water courses.

SHELF LIFE

1 year in original, unopened container, if stored in accordance with above recommendations.

● Specification

Fully written model propriety specifications for Glixtone products are available from the Glixtone Technical Services Department.

Additional Information

For further information, advice or guidance regarding any aspect of Glixtone products, please contact the Technical Services Department at the address below:

QUALITY CONTROL

All Glixtone products are checked before release using the latest techniques to ensure controlled, consistent high quality.

TECHNICAL ASSISTANCE

For further information, advice or guidance regarding any aspect of Glixtone products, please contact the Technical Services Department at the address below.

WARRANTY

As Glixtone has no direct control over the methods employed by the user in applying its products, any warranty either written or implied, is given in good faith and can only cover the material itself.